TECHNICAL DATA SHEET

CIIFROL SPORT 4T HH SAE 10W 30

High Performance Motorcycle Oil – API SL / JASO MA2

DESCRIPTION

Ciifrol Sport 4T HH SAE 10W-30 is high performance 4 stroke motorcycle oil manufactured with advanced additive technology to meet the stringent requirements of modern 4 stroke scooters and motorcycles. The advanced formulation protects Engine and Gear box while reducing Clutch slippage. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards

PERFORMANCE STANDARDS

SPECIFICATIONS	SAE VISCOSITY GRADE SAE 10W 30
API SL	✓
JASO MA: 2	✓

KEY PERFORMANCE FEATURES AND BENEFITS

- Superior high speed engine protection to extend engine life.
- Satisfies the lubrication requirements of a wide variety of engine cubic capacities.
- Extreme protection at high temperatures and heavy loads.
- Outstanding oil consumption control.
- Excellent wet clutch performance and protection of exhaust and catalyst systems.

APPLICATIONS

- 4 Stroke Motorcycles / Scooters

Ciifrol Sport 4T HH SAE 10W-30 is meant for use in all the latest generation scooters and motorcycles manufactured by reputed OEMs such as Honda, Bajaj, TVS, Mahindra and Yamaha, which recommend SAE 10W-30 viscometrics for fuel economy.

TYPICAL / CONTROL PROPERTIES

S. NO.	CHARACTERISTICS	ASTM	UNIT	CONTROL LIMIT
1.	Appearance	Visual	-	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	-	To Report
3.	Colour	D-1500	-	Natural
4.	K. Viscosity @ 40° C	D-445	CST	To report
5.	K. Viscosity @ 100° C	D-445	CST	12.5-14.5
6.	Viscosity Index	D-2270	-	110 min
7.	Flash Point COC	D-92	Deg C	200 min
8.	Pour Point	D-97	Deg C	-21 max
9.	TBN	D-2896	-	6.5-8.5

The information provided in this Technical Data Sheet is based on our best knowledge and experience and is intended as a general guide. The technical data represents typical values and may vary depending on product batches, operating conditions and application methods.

Users are advised to refer to the latest Technical Data Sheet and Safety Data Sheet (SDS) for applicable product information.

Users are advised to evaluate the product for suitability for their specific application and to follow recommended handling, storage and safety practices. CIIFROL accepts no responsibility for any loss, damage or injury resulting from improper, unintended or abnormal use of the product or conditions beyond its reasonable control.

Address: Plot No. 24, Sector 75, Vill. Darbaripur, Sub-Dist. Badshahpur, Dist. Gurugram, Haryana – 122101

Phone: +91 9727179657 | +91 7900794747 | +91 8822350009

Email: info@ciifrolglobal.com