TECHNICAL DATA SHEET

CIIFROL UNIVERSAL 4T SAE 20W 40

High Performance Motorcycle Oil – API SJ / JASO MA2

DESCRIPTION

Ciifrol Universal 4T SAE 20W-40 is specially tailored 4 stroke motorcycle oil manufactured with balanced additive technology to meet the requirements of modern 4 stroke scooters and motorcycles. The balanced advanced formulation protects Engine and Gear box while reducing Clutch slippage. These oils are recommended where the oil drain intervals are generally low and the oil is required to give satisfactory performance while providing economic advantage to the end user.

PERFORMANCE STANDARDS

SPECIFICATIONS	SAE VISCOSITY GRADE SAE 20W 40
API SJ	✓
JASO MA: 2	✓

KEY PERFORMANCE FEATURES AND BENEFITS

- Good high speed engine protection.
- Satisfies the lubrication requirements of 100–125 CC motorcycle.
- Good overall engine and gear protection.
- Excellent wet clutch performance and protection of exhaust and catalyst systems.

APPLICATIONS

- 4 Stroke Motorcycles / Scooters

Ciifrol Universal 4T SAE 20W-40 is meant for use in all types of scooters and motorcycles manufactured by reputed OEMs such as Honda, Bajaj, TVS, Mahindra and Yamaha.

TYPICAL / CONTROL PROPERTIES

S. NO.	CHARACTERISTICS	ASTM	UNIT	CONTROL LIMIT
1.	Appearance	Visual	-	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	-	To Report
3.	Colour	D-1500	-	Red
4.	K. Viscosity @ 40° C	D-445	CST	To report
5.	K. Viscosity @ 100° C	D-445	CST	13.5-15.5
6.	Viscosity Index	D-2270	-	110 min
7.	Flash Point COC	D-92	Deg C	200 min
8.	Pour Point	D-97	Deg C	-21 max
9.	TBN	D-2896	-	6.5-8.5

The information provided in this Technical Data Sheet is based on our best knowledge and experience and is intended as a general guide. The technical data represents typical values and may vary depending on product batches, operating conditions and application methods.

Users are advised to refer to the latest Technical Data Sheet and Safety Data Sheet (SDS) for applicable product information.

Users are advised to evaluate the product for suitability for their specific application and to follow recommended handling, storage and safety practices. CIIFROL accepts no responsibility for any loss, damage or injury resulting from improper, unintended or abnormal use of the product or conditions beyond its reasonable control.

Address: Plot No. 24, Sector 75, Vill. Darbaripur, Sub-Dist. Badshahpur, Dist. Gurugram, Haryana – 122101

Phone: +91 9727179657 | +91 7900794747 | +91 8822350009

Email: info@ciifrolglobal.com